



Technical Data Sheet

TYPE

PRODUCT

PRODUCT DATA

APPEARANCE

SOLVENT

NON-VOLATILE MATTER (%)

VISCOSITY [mpa·s] (25 °C)

OIL LENGTH

DENSITY [g/cm³], approx (25 °)

: Long Oil Alkyd Resin :

BENKYD LO 63W70 LV :

Transparent, slightly yellow :

White Spirit

: 70 ±2%

: 500 ~ 1500

: 63%

: 1.01

SPECIAL PROPERTIES AND USE

- Long oil air drying alkyd resin based on soybean oil. Excellent outdoor color durability and gloss retention; Very good brushability, very good through drying and hardening
- Air-drying all interior and exterior architectural Finishes, primers, and undercoats

PACKAGING

- In 200 KG net mild steel tight head drums.

Suggested drier combinations

-Cobalt	0,04-0,06%
-Zirconium	0,05-0,07%
-Calcium	0,08-0,10%

As metals on solid resin

Ben Kimya Dış Ticaret Limited Şirketi

Address: Aksu Yaşam Sitesi, Atatürk Mahallesi, 369.Sokak No:35, A2 Blok Daire:9

City: Kocaeli, District:Çayirova, Postal Code: 41420

info@benkimya.com / www.benkimya.com