

Technical Data Sheet

TYPE

PRODUCT

PRODUCT DATA

APPEARANCE

SOLVENT

NON-VOLATILE MATTER (%)

ACIDITY [mgKOH/g]

VISCOSITY [pa s] (25 °C)

DENSITY [g/cm³], approx (25 °C)

OIL LENGTH

COLOR

: Chain Stop Alkyd Resin

: BENKYD RAP 27X60

: Slightly yellow

: Xylene

: $60 \pm 2\%$

: Max 10

: $4\sim8$

 $1.00 \pm 0.02\%$

27

: Max 8

SPECIAL PROPERTIES AND USE

- Short oil air drying alkyd resin based on fatty acid. Excellent drying and durability; High gloss and glossretention; Resistance in humid conditions; Good mechanical properties.
- Very fast drying, high quality industrial primer and paints
- ➤ Hammertone Paints and Road Marking paints

PACKAGING

➤ In 200 KG net mild steel tight head drums.

Suggested drier combinations

-Cobalt 0,04-0,06% -Zirconium 0,05-0,07% -Calcium 0,08-0,10%

As metals on solid resin

Ben Kimya Dış Ticaret Limited Şirketi

Address: Aksu Yaşam Sitesi, Atatürk Mahallesi, 369. Sokak No:35, A2 Blok Daire:9

City: Kocaeli, District: Cayırova, Postal Code: 41420

info@benkimya.com / www.benkimya.com