



Technical Data Sheet

TYPE	: Urethane Alkyd Resin
PRODUCT	: BENKYD U 62W60
<u>PRODUCT DATA</u>	
APPEARANCE	: Transparent, slightly yellow
SOLVENT	: White Spirit
NON-VOLATILE MATTER (%)	: 60 $\pm$ 2%
VISCOSITY [Gardner] (25 °C)	: Z1 ~ Z2
OIL LENGTH	: 62%
DENSITY [g/cm ³], approx (25 °)	: 0.96 $\pm$ 2

SPECIAL PROPERTIES AND USE

- It is a TDI(toluene diisocyanate) modified urethane alkyd resin in white spirit, 60% solids.
- Used in the production of parquet varnish and yacht varnish.

PACKAGING

- In 180 KG net mild steel tight head drums.

Suggested drier combinations

-Cobalt	0,04-0,06%
-Zirconium	0,05-0,07%
-Calcium	0,08-0,10%

As metals on solid resin

Ben Kimya Dış Ticaret Limited Şirketi
Address: Aksu Yaşam Sitesi, Atatürk Mahallesi, 369.Sokak No:35, A2 Blok Daire:9
City: Kocaeli, District:Çayirova, Postal Code: 41420
info@benkimya.com / www.benkimya.com